# Eco Mark Product Category No. 125

# "Garbage Disposer Version1.6" Certification Criteria

Applicable Scope-A. Compost containersB. Home garbage disposers

Containers designed to decompose organic wastes with biological treatment at home and those which do not use energy such as electricity are classified into A.Compost containers, and garbage disposers of biological type or dry type designed for the above purpose which use energy such as electricity are classified into B. Home garbage disposers.

Established: Decem Last revised: Februa Expiration date March

December 18, 2002 February 1, 2023 March 31, 2031 Japan Environment Association Eco Mark Office

NOTE: This document is a translation of the criteria written in Japanese. In the event of dispute, the original document should be taken as authoritative.

# Eco Mark Product Category No.125 "Garbage Disposer Version1.5" Certification Criteria B. Home garbage disposers

Japan Environment Association Eco Mark Office

#### 1. Purpose of Establishing Criteria

The Certification Criteria of Eco Mark Product Category "Composting Containers," established in 1989, was intended to disseminate the use of systems to compost organic wastes, mainly with the functions of microorganisms. In 1994, electric systems were added to this product category to further spread these systems.

In the certification criteria of this product category, composting systems are defined, "(1) The product shall be a device for composting garbage mainly through the action of microorganism," and therefore have eliminating systems intended for drying or reducing organic wastes from the scope of applicable products. However, due to an increasing need for the reduction of household wastes in recent years, it was decided in the Eco Mark Committee for Product Certification meeting held in May 2000 that the scope of applicable products and certification criteria would be reviewed, and submitted to the Eco Mark Committee for Establishing Category and Criteria.

Organic wastes are referred to as food waste in documents released by the Ministry of Agriculture, Forestry and Fisheries, disposed by food manufacturers, food distributors, restaurant industry, and households. According to estimates by the Ministry of Agriculture, Forestry and Fisheries in documents released by the former Ministry of Health and Welfare in 1996, of the 19,400,000 tons of food waste that were disposed of, 91% or 17,720,000 tons were incinerated and buried. Because it is important to control the generation of a massive volume of food waste and to reuse it, the Law Concerning Promoting to Recover and Utilize Food Resources was enforced. In this product category, the environmental load resulting from organic wastes against this background was reviewed. The results confirmed that organic wastes disposed of by general composting systems are able to serve as the raw material of composting, etc. instead of fertilizers and compost. To reuse as compost, it needs to be processed an additional time. Consequently, in order to reduce the volume of organic wastes, it is important to reduce wastes as well as perform interim process for effective reuse. In addition, since the composting system may reduce energy consumption during garbage incineration, it was decided that the scope of application of composting systems would be reset, the reduction and reuse of organic wastes promoted, and the supply of information on organic waste volume reduction enhanced. To evaluate the product life cycle, the environment load resulting in the manufacture and usage of the composting system was reviewed and the appropriate certification criteria were established

125B V1 Criteria

# 2. Applicable Scope

Garbage disposers of biological type or dry type designed to decompose organic wastes at home and those which use energy such as electricity. Collective compost containers used in housing complexes are excluded.

## 3. Terminology

Biological type	Method of decomposing organic wastes using microorganisms in				
	aerobic conditions to reduce volume.				
Dry type	Method of drying organic wastes using energy such as electricity				
	to reduce volume.				
Home garbage	Biological and dry disposing systems designed for home disposal of				
disposer	organic wastes. These use energy like electricity and exclude				
	collective garbage disposers found in housing complexes				
Base material	Made of multi-porous wood, pulp, or other similar materials. Used				
	for the purpose of maintaining aerobic decomposition conditions.				

# 4. Certification Criteria and Certification Procedure

4-1. Environmental Criteria and Certification Procedure

(1) The standard power consumption of the system shall be below 1.5 kWh/kg at this time.

[Certification Procedure]

The power consumption of the concerned systems shall be indicated in the Attached Certificate. Power consumption measurement shall conform to Composting System Performance Evaluation Criteria and Performance Guidelines.

(2) Foamed plastic shall not use the specific CFCs (5 CFCs), other CFCs and HCFC listed in Attachment 1.

[Certification Procedure]

Whether the plastic and the foaming agents are used is indicated in the Attached Certificate. If they are used, whether fluorocarbons listed in the Attachment 1 are used is also indicated in the Attached Certificates.

(3) Home garbage disposers must be designed with consideration to facilitating the recycling of wastes.

[Certification Procedure]

Explanatory documents for the recycle design shall be submitted.

(4) The User's Manual shall provide the information listed in Attachment 2.

[Certification Procedure]

The User's Manual containing the information listed in Attachment 2 shall be submitted.

(5) The User's Manual and the product label or pamphlet hall specify the maximum power consumption in the operating state.

[Certification Procedure]

The corresponding sections of the User's Manual and the product label or pamphlet shall be submitted.

(6) In manufacturing the applied product, related environmental laws and regulations and pollution control agreement (hereinafter referred to as the "Environmental Laws, etc.") must be followed with respect to air pollution, water contamination, noise, offensive odor, and emission of hazardous materials in the area where the plant performing the final manufacturing process is located.

In addition, the state of compliance with the Environmental Laws, etc. for the last five years from the date of application (whether there is any violation) must be reported. If there is any violation, it is necessary that proper remedies and preventive measures have been already taken, and the related Environmental Laws, etc. must thereafter be followed appropriately.

[Certification Procedure]

With respect to the compliance with the Environmental Laws, etc. in the area where the plant performing the final manufacturing process is located, a certificate issued by the representative of the business of manufacturing the applied product or the manager of the relevant plant (entry or attachment of the list of names of the Environmental Laws, etc.) must be submitted.

In addition, it is necessary to report whether there is any violation during the last five years, including a violation subject to administrative punishment or administrative guidance, and if there is, the following documents in a and b must be submitted:

- a. With respect to the fact of violation, guidance documents from administrative agencies (including order of correction and warning) and copies of written answers (including those reporting causes and results of correction) to such documents (making a series of progress clear);
- b. Following materials (copies of recording documents, and so on) concerning the

management system for compliance with the Environmental Laws, etc. in 1)-5):

- 1) List of the Environmental Laws, etc. related to the area where the plant is located;
- 2) Implementation system (organizational chart with entry of roles, etc.);
- 3) Document stipulating retention of recording documents;
- 4) Recurrence prevention measures (future preventive measures);
- 5) State of implementation based on recurrence prevention measures (result of checking of the state of compliance, including the result of onsite inspection).

(7) Polybrominated biphenyl (PBB), polybrominated diphenyl ether (PBDE), or chlorinated paraffin (chain carbon number of 10 to 13, with chlorine concentration above 50%) shall not be added to plastic or printed-circuit boards as prescription constituents. Printed-circuit boards are printed boards that do not incorporate semiconductors.

[Certification Procedure]

Whether the plastic and the foaming agents of printed-circuit boards are used and whether PBD, PBDE and chlorinated paraffin are used is indicated in the Attached Certificate. In addition, parts procurement contracts, etc. shall be submitted to certify that PBB, PBDE, and chlorinated paraffin have not been added.

(8) Base materials shall be carefully kept from containing hazardous chemicals.

[Certification Procedure]

Raw materials of the base material shall be specified in the Attached Certificates.

4-2. Quality Criteria and Certification Procedure

(9) Performance shall be verified in accordance with the "Home garbage disposer Performance Evaluation Criteria and Performance Guidelines" at the end of this Criteria or any quality standards equivalent to this. Quality control should also be implemented adequately at the manufacturing stage.

[Certification Procedure]

A certificate indicating conformity to the corresponding quality criteria shall be submitted. At the same time, a certificate issued by the manager of the plant manufacturing the product, stating that quality control is being implemented adequately and no laws have been violated in the manufacturing stage, shall be submitted. 5. Product Classification, Indication and Others

(1) Product classification (application unit) shall be by model or by series of model. In case of product classification by series of model, several models may be placed under the same application, however, each model in the series shall conform to the relevant criteria.

(2) In principle, the Eco Mark shown as below shall be indicated on the product, etc. The licensees of Eco Mark Utilization Contract who own the Eco Mark products shall also be allowed to use the indication and the certification number as before.



(Note for the indication)

- \*For indicating the logo, Eco Mark certification number (eight-digit number) or the name of the licensee using the logo shall be appeared.
- \* Such expression as "Eco Mark product" can be used following the 2.(2) of the Guide to Eco Mark Usage.
- "Eco Mark product", "#Eco Mark", "www.ecomark.jp", "Eco Mark Certificate"
- \* In accordance with "Environmental Labeling Guidelines" of the Ministry of the Environment of Japan, etc., the environmental claims of certified products may be indicated in association with Eco Mark

(https://www.env.go.jp/policy/hozen/green/ecolabel/guideline/).

\* The Guide to Eco Mark Usage shall be followed for any cases not listed above.

(https://www.ecomark.jp/office/guideline/guide/)

(3) Environmental claims such as advertisements should be based on verifiable data (claims such as complete disappearance should be avoided). Brochures or other advertisements should be submitted for this item.

December 18, 2002	Established
Dec. 26, 2003	Revised (Eco Mark Usage)
February 12, 2004	Revised (addition of criteria regarding to flame
	retardants)
July 1, 2004	Revised (indication below Eco Mark Version1.1)
November 1, 2004	Revised
August 3, 2006	Revised

October 19, 2006	Revised Version1.2
October 5, 2007	Revised
August 21, 2008	Revised Version1.3
March 1, 2011	Revised Version1.4
July 13, 2012	Revised Version1.5
April 1, 2015	Extension of Expiration date
January 7, 2019	Extension of Expiration date
April 1, 2019	Revised (Eco Mark indication)
February 1, 2023	Revised (Category A 4-1.(1),(2) Version1.6)
March 15, 2024	Extension of Expiration date
March 31, 2031	Expiration date

The Certification Criteria for the Product Category will be revised when necessary.

# Attachment 1

Substances prescribed in 4-1. (10)					
Specified CFCs	trichlorofluoromethane				
(5  CFCs)	dichlorodifluoromethane				
	trichlorotrifluoroethane				
	dichlorotetrafluoroethane				
	Chloropentafluoroethane				
Other CFCs	Chlorotrifluoromethane				
	Pentachlorofluoroethane				
	Tetrachlorodifluoroethane				
	Pentachlorofluoropropane				
	Hexachlorodifluoropropane				
	Pentachlorotrifluoropropane				
	Tetrachlorotetrafluoropropane				
	Trichloropentafluoropropane				
	Dichlorohexafluoropropane				
	Chloroheptafluoropropane				
	Carbontetrachloride				
	1,1,1-trichloroethane				
CFCs substitute (HCFC)	Dichlorofluoromethane				
	Chlorodifluoromethane				
	Chlorofluoromethane				
	Tetrachlororfluoroethane				
	Trichlorodifluoroethane				
	Dichlorotrifluoroethane				
	Chlorotetrafluoroethane				
	Trichlorofluoroethane				
	Dichlorodifluoroethane				
	Chlorotrifluoroethane				
	Dichlorofluoroethane				
	Chlorodifluoroethane				
	Chlorofluoroethane				
	Hexachlorofluoropropane				
	Pentachlorodifluoropropane				
	Tetrachlorotrifluoropropane				
	Trichlorotetrafluoropropane				
	Dichloropentafluoropropane				
	Chlorohexafluoropropane				
	Pentachlorofluoropropane				
	Tetrachlorodifluoropropane				
	Trichlorotrifluoropropane				
	Dichlorotetrafluoropropane				
	Chloropentafluoropropane				
	Tetrachlorofluoropropane				
	Trichlorodifluoropropane				
	Dichlorotrifluoropropane				
	Chlorotetrafluoropropane				
	Trichlorofluoropropane				
	Dichlorodifluoropropane				
	Chlorotrifluoropropane				
	Dichlorofluoropropane				
	Chlorodifluoropropane				
	Chlorofluoropropane				

# Attachment 2 Particulars Required in User's Manual on Home garbage disposers

The following shall be taken into consideration when writing descriptions in the User's Manual

- Disposed wastes that have been reduced in volume (hereafter referred to as disposed wastes) can serve as the raw material of compost, instead of compost itself.
- Each user should be individually responsible for the disposal of wastes.

The User's Manual shall provide the following information for the compost container to achieve sufficient performance.

# 1. Manufacturer (logo if possible), product name and number shall be indicated.

# 2. Indications to ensure safety (Safety precautions)

Warning and cautions to ensure safe use and prevent injuries and damage to assets in use of the product shall be provided (They are not applicable in the case of malfunction or insufficient performance due to defect of the product.)

# 3. Name and function of main parts

Drawings and photographs shall be used to describe the names and functions of main parts requiring sufficient understanding of users prior to use.

# 4. Installation (Installing method)

The site and method of installation shall be indicated. Units to be installed outdoors shall describe potential risks if the disposer is used indoors.

# 5. Preparations (Prior to use)

The procedure for preparing to use the system such as checking and connecting components and accessories shall be described specifically.

# 6. Precautions on use

Handling precautions on causes of malfunctions and damage to the product, acts which disable the product from achieving the required functions and performance shall be indicated.

[Examples]

- Waste etc. that can be disposed and what cannot
- General troubleshooting

# 7. Using the system (How to use the system)

The method of using the system shall be explained clearly from the standpoint of the user.

[Examples]

- General principle on volume reduction
- Start of volume reduction
- Addition of organic wastes and base material

# - Stirring

- Temperature and humidity appropriate for volume reduction
- Appraisal on whether volume reduction was successful

# 8. Handling of disposed waste

The following information shall be included.

(1) Precautions on use for gardening

- (a) Use for home gardening shall be carried out at the user's own responsibility.
- (b) In the case of (a), the method of use recommended by the manufacturer (in
- the User's Manual) shall be followed.
- (c) Precautions for (a)
- When using as fertilizer, the compost shall be matured for a certain period of time as recommended. If dispersed without doing so, it may have adverse effects on plants.

-In particular, dispersing disposed waste which has been treated only for a short period of time will increase the risk of adverse effects on plants.

- (2) Precautions on storage over a long period of time
- (3) To throw away disposed waste, it can be treated as burnable garbage since its volume has been reduced.

# 9. Ideal way of using disposed waste

Any know-how and tips for effective use that will be more likely to produce the expected function and performance shall be indicated.

# 10. Replacement of parts (addition and replacement of base material)

For consumable parts (base material) that need to be added (replenished) or replaced, how to determine the time of addition and replacement, and replacement method, etc. shall be described.

# 11. Inspection

If any daily or periodic inspections are required to ensure ideal and safe use, why they are necessary and how they are carried out shall be provided.

# 12. Maintenance

To maintain product performance, the need for cleaning and maintenance and method shall be described.

# 13. Determining malfunctions (what to do when malfunction is suspected)

Guidelines (table) to determine if the system has malfunctioned when it stops operating normally in use and how to cope with the problem shall be provided.

# 14. Specifications

Product specifications such as power supply, electric power consumption, maximum power consumption, dimensions, and weight shall be described.

# 15. Options

Options sold separately (materials) for replacing or replenishing parts (materials), and expanding functions in the use of the product shall be described.

# 16. Guarantee and after-sales service

The following information shall be included.

- Guarantee
- Request for repair
- Period of time while repair parts are available shall be 6 years after the cease of manufacturing of the product
- Customer desk for inquires and repairs
- Precautions on safety inspection and safe use of products used over a long period of time

# 17. Manufacture information

The following items shall be included to clarify the responsibility for issuing the User's Manual.

- Company name
- Head office address and telephone number
- Name, address, and telephone number of product planning division

## 18. Others

The following shall be specified.

- Precautions taken when filling container (recommended)
- Remove moisture (roll in newspaper, dry in windy place, dry in the sun)
- Better to cut up large wastes into smaller parts
- Be cautious about what to include (avoid including liquids (water), oil (do not include oil), fish/meat (protein), etc. in large amounts, because these cause odor)
- Handling microorganisms
- Aim not at rotting but volume reduction.
- For biological composting, precautions on possibility of contamination by microorganisms and population fluctuations in indoor use (sealed off space) shall be added.

## Home Garbage Disposer Performance Evaluation Criteria and Performance Guidelines

## 1. Product definition

(1) System

A system that reduces the volume of organic waste efficiently using electric energy.

A secondary advantage of the system is that it can convert the disposed waste into reusable resources such as raw materials for composts. There are biological and dry systems.

(2) Processing object

Organic wastes disposed from households.

The approximate volume of wastes disposed per day is 300-3,000 grams.

(3) Rated voltage

The commercial AC power is 100 V or 200 V.

(4) Site

For installation in general households (apartments and houses). Indoor and outdoor types are available.

## 2. Test conditions

The test conditions are as follows (the same for all items):

Temperature:  $20\pm2$  °C

Humidity:  $60\pm10\%$ 

Voltage: 100V or 200V (based on rated voltage)

Frequency: 50H z, 60H z

Applicable wastes: Standard test organic wastes of the standard quantity are filled into the system. In addition, 700 grams (average weight of organic wastes per day for a family of four.) can be measured separately for reference. Note that "standard quantity" is the rated weight (g or kg) of organic wastes that can be treated smoothly every day in the standard operating conditions of the system for the designated nominal term.

> For the biological system using aerobic fermentation, "can be treated smoothly" requires the condition that the moisture content of the base material should be below 75% to control the anaerobic fermentation state that occurs in high moisture levels. When the high moisture level continues, the aerobic fermentation state usually shifts to anaerobic fermentation state, and the emission from the base material changes from the normal ammonia gas to malodorous acetic gas. For the dry type, the rated quantity of organic wastes shall be filled in the system to ensure sufficient dryness.

Replacement of base material: Criteria for replacement of base materials of the

biological type depend on the manufacturers' decision.

#### 3. Power load and power consumption

#### 3-1. Power load

The maximum power load is the watt measured in operating conditions with maximum load imposed. (Operating condition with the maximum load imposed is the condition in which the system can demonstrate maximum performance within the operating temperature range. In other words, it is the operating mode in which the system is filled with the maximum possible quantity of organic wastes, and where it can demonstrate other added functions the most <deodorize function, etc.>.)

#### 3-2. Power consumption

- (1) The power consumption is the electric energy consumed from start to end of treatment of the standard test organic wastes (standard quantity) filled into the system in the standard operation conditions of the system.
- (2) The power consumption of the biological type is affected by the treatment state of the base material and atmospheric temperature. Therefore, the standard test organic materials of the standard quantity are filled into the system every day based on "2. Test conditions" above to stabilize the treatment state. A watt-hour meter is used to measure the integral power for one week in the stable processing state. Electric energy used daily, or power consumption, is calculated using the measurement. The "stable processing state" for the biological system is nearly equivalent to the state two weeks after continuous supply of organic wastes.

#### 4. Reduced mass rate

- (1) The percentage that indicates how much the organic wastes filled into the system (g or kg) has been reduced after treating standard test organic wastes of standard quantity.
- (2) The reduced mass rate is measured for the nominal time with the dry type and for 2 months with the biological type.
- (3) With the biological type, measurement is done at two months when the reduced mass rate stabilizes.
- (4) Calculation equation

Reduced mass rate (%) = [total quantity of organic waste (kg) - {total mass at end of test (kg) - total mass before test (kg)}] / total quantity of organic wastes (kg) x 100

(5) As the performance of the biological system varies according to the measuring conditions such as region, season, and temperature and humidity of the operating environment, the note "performance varies according to measuring conditions such as region, season, and temperature and humidity of the operating environment" shall be added.

(6) The reduced mass rate should be at least 70% in the above tests.

#### 5. Treatment time

This is the index on the treatment speed of organic wastes. It is the time from the start of processing after standard test organic wastes are filled into the system to the end of the process.

With the dry type, it is the time until the designed dry rate is achieved or the operating time that can be preset using a timer.

With the biological type, it is the operating time until the "state in which the form of the standard test organic waste is no longer identifiable" is achieved.

However, the treatment time of the biological composting varies diversely according to the type of organic waste, composition, size, and freshness. In actual use, as the organic waste can be filled into the system over a long period of time until the time of replacement of the base material, the length of the treatment time is insignificant. Consequently, the treatment time for standard test organic wastes is merely a reference for processing speed and should be treated carefully.

If the length of the treatment time is at issue in the biological system, the type, composition, size, and freshness of the organic waste shall be clearly indicated: for instance, "Treatment time of boiled cabbage center measuring 3 cm in size is three days."

From these reasons, it is appropriate to indicate the processing speed per time for the dry type and the standard processing quantity per day for the biological type.

### 6. Noise

(1) Noise generated during the operation of the composting system.

- (2) Measuring conditions are based on characteristics A of JIS Z 8731 noise level measuring method.
- (3) Supposing the system is operated in the standard state, noise levels are measured 1 m away from the system at the front, right, and left sides, and the average value is calculated. The height is the center of the system.
- (4) Noise is measured for every operation when it changes due to operating states such as stirring and ventilation. It is measured for every frequency when it changes due to power frequency, and the maximum value is indicated.

#### 7. Measures taken for odor

The product shall be deodorized and left open to the extent that it does not affect the peripheral environment and residents. To deal with the issue of odor, the following methods can be used; catalytic deodorizing system, aerobic microorganism treatment, microorganism deodorizing method using specified bacteria, dilution, duct emission, adsorption, electric discharge deodorization.

## 8. Safety

The system shall be designed with a safety structure conforming to the electric equipment safety law, and appropriate warning notes and precautions shall be labeled on the system or provided in the User's Manual to ensure safe use of the product. (Equivalent to JEMA Anzen Hyoji Jissi Yoryosho (guidelines on safety signs and indications)

		<u>W</u> a	<u>astes</u>			
		Actual organic waste	ratio			
Waste Composition		(weight ratio)		Method of cutting		
				Cut into pieces of less than 10 mm		
		Cabbage 25		in width (including center)		
	Vegetable			Cut into quarters and then into		
	skin/scrap/	Potato	<b>5</b>	small pieces of 5 mm (with skin)		
е	center			Cut into halves and then into small		
abl	(leftover)	Onion	5	pieces of 5 mm (including skin)		
eta				Cut into quarters and then into		
Veg		Radish	<b>5</b>	small pieces of 5 mm		
				Cut into eight pieces vertically		
	Fruit	Apple	15	(including center)		
	skin/center			Cut into eight pieces vertically		
		Orange or tangerine	15	(with skin)		
	Sub Total		70			
				Chopped into irregular pieces		
at	Meat	Raw meat	3	around 3 cm		
Iea	Fish	Raw fish (sardine, etc.)	) 8	Cut into quarters		
	Egg shell	Chicken egg shell	2			
	Sub Total		13			
Vegeta	ble and meat					
total	-		83			
Other	Leftover food	Rice or <i>udon</i> noodle	11			
	Tea dregs	Tea dregs	6	Used tea leaves		
	Sub Total		17			
	Total		100			

Types,	Contents,	and Processing	g methods	of Foods	Used for	Standard	Test Organic

\*The composition of the organic wastes above is based on the following survey results, but may be revised with lifestyle changes.

<References>

1. Survey Report of Sewerage and Sewage Purification Department, Ministry of Land, Infrastructure and Transport

- 2. Survey Report of Bureau of Sewerage, Tokyo Metropolitan Government
- 3. Kyoto City Household Waste Disposal Survey Report
- 4. Nara Women's University Household Waste Survey
- 5. Survey by Composting System Monitors