

Eco Mark Product Category No.131
“Products for Civil Engineering Version 1.20” Certification Criteria
Category I. Materials for bridges/rivers/harbors

Japan Environment Association
Eco Mark Office

1. Purpose of Establishing Certification Criteria

In civil engineering/construction-related business that is implemented as part of social infrastructure development, ripple effects in the economy are expected, but at the same time a significant environmental load is imposed on the natural environment of the oceans, rivers and land as well as the living environment. New forms of civil engineering-/construction-related business based on the principles of the “Basic Environmental Law,” such as through harmonization with the natural environment, formation of a good living environment, prevention of global warming by improving energy efficiency, etc., are therefore being explored.

In addition to these kinds of environmental conservation efforts, it was also determined that in the civil engineering/construction-related business it is necessary to promote the control of waste generation (reduction), secondary uses (reuse) and recovery for further use (recycling) in accordance with the “Waste Disposal and Public Cleansing Law,” the “Basic Law for Establishing a Recycling-Based Society,” the “Law Concerning Promotion of the Procurement of Eco-friendly Goods and Services by the State and Other Entities (Green Procurement Law)” and the “Law for Recycling Materials for Construction (Construction Recycling Law).” Furthermore, independent efforts by civil engineering/construction enterprises for reduction of the environmental load, the “Guidelines for Green Procurement in the Construction Industry” were formulated in 2002.

In Japan’s material balance, the proportion attributable to civil engineering and construction-related business accounts for approximately 40% of new resources (2002 White Paper on a Recycling-Oriented Economic System; FY2001 Major Construction Materials Demand Forecast), approximately 20% of industrial wastes and approximately 40% of wastes collected at final landfill sites (2002 Environmental White Paper). It can therefore be expected that an environmentally-sound materials cycle to promote reduction, reuse and recycling will have a major impact on the structure of society.

The load placed on elements of the environment by the civil engineering and construction-related business varies according to many environmental factors such as the site of the business and the methods and types of materials used. As the environmental load may be reduced by applying Eco Mark Product Certification to construction materials, one of the factors affecting this, the Eco Mark Certification Criteria for newly applied products, shall be established to certify such materials as ‘construction products’ after organizing and integrating them with products that are already certified.

The new certification criteria, in addition to minimizing the consumption of new materials and the generation of wastes on the basis of using recycled materials, as has been recommended, and taking into consideration the reduced use of hazardous substances, energy saving, the impact on the ecosystem, etc., that are intended to reduce the environmental load imposed by construction work and long-term use, both of which may be characteristic of construction products, aim at the same time to achieve a symbiotic relationship with nature by creating a secondary natural environment. The concept of the life cycle of materials and products will be introduced into the evaluation, taking into consideration the life stage when the construction work is commenced as a construction product, and as many concrete environmental load items as possible have been selected.

2. Applicable Scope

Rubber materials for harbors(Fenders/rubber ship gangways/Corner protection materials / Slip prevention fences), Harbor embankment mats, Wire-cylinders, Special type mat cylinders, Impermeable-type steel erosion control weirs, Permeable-type steel erosion control weirs, Steel sheet piles with pots for bank protection and tree planting, Fish-breeding reefs and base materials for breeding, channel repairing panel

3. Terminology

Terms for the common standard

| | |
|-------------------------|--|
| Recycle | Materials recycling only; energy recovery (thermal recycling) is not included. |
| Recycled materials | Post-consumer materials or pre-consumer materials, or a combination of these. However, this product category shall include thinned wood, less useful wood, slag resulting from industrial activities, etc., in recycled materials. |
| Pre-consumer materials | Materials or rejected products generated from a disposal route in a product manufacturing process, excluding those that are recycled within the same process (plant). |
| Post-consumer material | Material or product which was disposed of after being used as a product |
| Standard mixture amount | The percentage of recycled materials of each material that is used to manufacture products (as % by mass), and calculated as follows and regulated on a material-by-material basis: Standard mixture amount = recycled materials/each material |
| Prescribed constituents | Material components added for the intended purpose of giving certain characteristics to the products. Impurities that are technically unavoidable in the manufacturing process are not included. |

| | |
|---------------------|---|
| Waste rubber | Post-consumer materials and pre-consumer materials obtained from used tires, tubes, etc. |
| Construction sludge | Construction sludge prescribed in the “Appropriate Disposal of Waste Produced from Construction Work” (Kansantasu No. 26, June 11, 2001). |

Terms for paper

| | |
|---|---|
| Waste paper | Collected post-consumer waste paper and pre-consumer waste paper. |
| Post-consumer waste paper | Used paper generated in shops, offices, or households. |
| Pre-consumer waste paper | <p>Paper diverted from the waste stream during the processing stage at facilities which use paper for material such as paper processing factories, paper products factories, printing and bookbinding plants.</p> <p>However, if waste paper resulting from the paper making process in a plant or works of a party (hereinafter referred to as “paper manufacturer”) that conducts business related to the paper manufacturing industry (hereinafter referred to as “plants, etc.”) or those resulting when processing, etc. is performed in the plants, etc. of the paper manufacturer (including the case in which the paper manufacturer has other contractor to conduct processing through commissioning of the product before its shipment) is not shipped as a product, and used as raw material for papers by the paper manufacturer, they shall not be treated as waste paper (from “Regarding operation of ministry ordinances, etc. defining matters that should be criteria for judgment on use of waste paper of those who conduct business related to the paper manufacturing industry” of the Ministry of International Trade and Industry dated December 24, Heisei 3 (1991).</p> |
| Percentage of waste paper in the pulp mixture | Weight percentage of waste pulp in pulp contained in product. Expressed by (waste paper pulp) / (virgin pulp + waste paper pulp) x 100 (%). However, the weight of the pulp is measured under the condition of containing 10% moisture. In addition, waste sheets shall not be included in the denominator and numerator, respectively, of the calculating formula of waste paper pulp combination rate. |

Terms for wood

| | |
|--------------------|---|
| Reused/Unused wood | Indicates the following: forest thinnings, waste wood, construction waste wood, and less useful wood. |
|--------------------|---|

| | |
|-------------------------|--|
| Thinned-out log | Wood produced from a reduction in the density of the tree type that is the objective of management based on the intensity of the forest stand |
| Waste wood | Used wood (used packing materials, etc.), remainder materials generated in wood processing plants (shavings generated in plywood/lumber plants, etc., low quality chips not used as raw materials for paper, etc.), and wood and wooden materials such as trimmed branches, bark, etc. |
| Construction waste wood | Wood and wooden materials disposed of as waste during construction work such as from the dismantling of buildings, construction of new buildings, building extensions, renovations, and construction related to other work. |
| Less useful wood | Abandoned lumber in the forest, shrubs, tree roots, wood obtained from lumber damaged by disease, pests, disasters, bent or small diameter logs, etc. Also includes bamboo cut down in bamboo groves for the purpose of maintenance and management in environment preservation. Small diameter logs measuring less than 14 cm in diameter corresponding to “a” or “b” below must be certified as forests sustainably managed by an independent third party or public organization. a. Small diameter logs from logs felled from natural forests. b. Small diameter logs from logs produced by clear cutting, patch logging, and strip logging in plantation forests. |
| Waste plant fiber | Agricultural residues generated during harvesting and the manufacturing process such as rice hulls, and used packaging materials such as jute bags, etc. |
| Wooden part | Actual wood (including plant fibers) |

Terms for glass

| | |
|----------------------------------|--|
| Glass cullet | Waste glass used as materials for making new glass and given recycling treatment (sorting, removal of foreign matter, etc.). |
| Percentage of glass cullet usage | The rate of the total amount of glass material used in a product, which is calculated as follows and all materials shall be expressed by mass: Glass cullet/total amount of glass material (per product) |

Terms for plastic

| | |
|--|---|
| Plastics: | Materials composed of a single or multiple polymers, plus additives, fillers, etc. that are added to the polymer(s) to give it (them) specific characteristics. |
| Recycled plastic: | Plastic materials composed of post-consumer materials and pre-consumer materials. |
| Plant-based plastic | Plastic made of bio-based synthetic polymer whose materials are plant. This certification criteria covers polyethylene (PE), polyethylene terephthalate (PET), polylactic acid (PLA) and polytrimethylene terephthalate (PTT). |
| Bio-based synthetic polymer | “Biobased synthetic polymer” defined in ISO 16620-1 3.1.4 (original: polymer obtained through chemical and/or biological industrial process(es) wholly or partly from biomass resources). |
| Bio-based synthetic polymer content rate | Content rate of biomass resources in bio-based synthetic polymer which is included in a product (or a designated portion by certification criteria). Means bio-based synthetic polymer content (Original sentence: bio-based synthetic polymer content : amount of bio-based synthetic polymer present in the product) defined by ISO 16620-1 3.1.5 |

Terms for fiber

| | |
|-----------------------------|--|
| Unused fiber: | Cotton linter and short fibers produced during spinning. |
| Recycled fiber: | Recovered fibers, recycled polymer fibers or recycled chemical fibers. |
| Recovered fiber: | Fibers of recovered materials such as lint from fabric factories, cutting waste from sewing factories and used clothing (including split-and-weave textiles). |
| Recycled polymer fiber: | Fibers produced from recycled resin using recycled shreds of post-consumer materials and pre-consumer materials, or pellets.- |
| Recycled chemical fiber: | Fibers composed of polymers produced from polymerized monomers as raw materials that were obtained by depolymerizing/polymerizing used products of nylon or polyester materials or polymers of pre-consumer materials. |
| Recycled cloth: | Cloth produced by cutting rejected cloth during inspections, used clothing and old cloth. |
| Plant-based synthetic fiber | Synthetic fiber whose material is plant-based plastic |

4. Certification Criteria and Certification Procedure

Any certification verifying conformity with the criteria shall be signed by the

applicant and submitted.

4-1. Environmental Criteria and Certification Procedure

4-1-1. Common criteria and certification procedure

(1) In manufacturing the applied product, related environmental laws and regulations and pollution control agreement (hereinafter referred to as the “Environmental Laws, etc.”) must be followed with respect to air pollution, water contamination, noise, offensive odor, and emission of hazardous substances in the area where the plant performing the final manufacturing process is located.

In addition, the state of compliance with the Environmental Laws, etc. for the past five years from the date of application (whether there is any violation) must be reported. If there is any violation, proper remedies and preventive measures shall have been already taken, and the related Environmental Laws, etc. must thereafter be followed appropriately.

[Certification Procedure]

With respect to the compliance with the Environmental Laws, etc. in the area where the plant performing the final manufacturing process is located, a certificate issued by the representative of the business of manufacturing the applied product or the relevant plant manager (entry or Attachment of a list of names of the Environmental Laws, etc.) must be submitted.

In addition, the applicants shall report whether there is any violation in the past five years, including a violation subject to administrative punishment or administrative guidance, and if there is, the following documents in a and b must be submitted:

- a. With respect to the fact of violation, guidance documents from administrative agencies (including order of correction and warning) and copies of written answers (including those reporting causes and results of correction) to such documents (clearly indicating a series of communication);
- b. Following materials (copies of recording documents, etc.) concerning the management system for compliance with the Environmental Laws, etc. in 1)-5):
 - 1) List of the Environmental Laws, etc. related to the area where the plant is located;
 - 2) Implementation system (organization chart with roles, etc.);
 - 3) Bylaws stipulating retention of recording documents;
 - 4) Recurrence prevention measures (future preventive measures)
 - 5) State of implementation based on the recurrence prevention measures (check results of on-site inspection, etc. as compliance condition).

4-1-2. Material criteria and certification procedure

The constituents of the products shall conform to the following criteria for the respective materials. In this regard, the relevant criteria for the materials shall not be applicable to minor attachments (minor parts necessary for the functioning of the product, such as screws, adhesives, etc.).

A. Wood

- (2) For products using lumber from dismantled buildings (wood and wooden materials disposed in dismantling), materials subject to preservatives, termicides, and pesticides shall be differentiated and eliminated. The content of harmful substances in these products shall meet the requirements for hexavalent chromium and arsenic given in Attached Table 5, which is provide by the detailed enforcement regulations (December 26, 2002, Environment Ministry Ordinance No. 29) of the Soil Pollution Control Law.

[Certification Procedure]

Documents certifying that wood from dismantled buildings is sorted in use or not used (work manual, workflow, etc.) shall be submitted. If using such waste wood from dismantled buildings, results of tests performed by a third party testing centers or public institutions shall be submitted.

- (3) Wood preservatives shall be approved by the Japan Wood Preserving Association.

[Certification Procedure]

The use of wood preservatives shall be described in the Application Form for Eco Mark Certification for details. A document stating the reasons for their use and certifying that the preservative agents have been approved by the Japan Wood Preserving Association shall be submitted.

- (4) If paper (virgin pulp) and wood are used as the material, the raw wood shall be harvested in legally appropriate procedure consistent with the forest laws of timber producing countries or regions. However, this item is not applicable for waste wood, construction waste wood or less useful wood.

[Certification Procedure]

A certificate shall be submitted to prove that the timber whose legality has been verified* in accordance with “Guideline for Verification on Legality and Sustainability of Wood and Wood Products” of Forestry Agency has been in custody to be separated by the applicant or the paper manufacturer and is supplied to the applied products. At the same time, the applicant or the paper manufacturer who issues the above certificate shall submit any of the following certificates:

- 1) Certificate that the applicant or the paper manufacturer has been assessed and authenticated by the CoC (Chain of Custody) Certification System;
- 2) Certificate of the authorized company (that guarantees the association member’s adequate way of supplying wood and wood products verified with legality, etc.); and
- 3) Code of management practice which stipulates the way of custody to manage wood and wood products verified with legality (the method in the case that the timber verified with legality only is handled. The same applies to hereunder), retention of certificates for a predetermined period, etc.

In the event that Item 2) or 3) above is chosen and the certificate is submitted, the applicant who issues the above-mentioned certificates or the material

supplier shall publicly announce through its web site the code of management practice prescribed by the association concerned in the case of Item 2) and shall prescribe and publicly announce through its website the code of management practice concerning the scheme to assess and guarantee the system for separative management, document management for retention of certificates for a predetermined period, etc. in the case of Item 3).

*Confirm the certificate issued by the related company closest in commercial process, which at least verifies that wood and wood products they supply are with legality and under separative custody management.

B. Plastics

- (5) Plastic additives shall follow positive lists specified by the industry's own standards.

As for the elution of harmful substances, the plastics shall conform to the standards concerning elution of harmful substances that are set forth in Attached Table 4 of the enforcement regulation of the Soil Contamination Countermeasures Law (2002 Ministerial Order No. 29 of the Ministry of the Environment) with respect to cadmium, lead, hexavalent chromium, arsenic, mercury, selenium, among the specified hazardous substances listed therein. In lieu of the requirements of the Enforcement Regulation of the Soil Contamination Countermeasures Law, conformance of the Product to the standards concerning hazardous substances set forth in ISO 8124-3 may be accepted.

In the case of using flame retardant, the product shall have no flame retardant of Polybrominated biphenyl (PBB), Polybrominated diphenylether (PBDE) or short-chain chlorinated paraffin (the number of chained C is 10 to 13 and contained chloride concentration is 50% or over) added as formulated components. In addition, (Pb)-based chemical compounds, cadmium (Cd)-based chemical compounds, tributyl tin compound (TBT), triphenyl tin compound (TPT), dibutyl tin compound (DBT), diphenyl tin compound (DFT), and monophenyl tin compound (MFT) shall not be added as prescribed constituents.

[Certification Procedure]

To show that the plastic resin (including recycled plastics) and plastic additives meet the requirement on the harmful materials, a certificate issued by the raw materials supplier, or a certificate describing the results of tests carried out by an independent testing institution shall be submitted. In cases where no raw materials contain any of the corresponding chemical substances as a prescribed constituent, a document prepared by the raw materials supplier and the applicant that proves there is no content of the chemical substance shall be acceptable..

- (6) In case of the product which is added the plastics containing halogen in polymer backbones as prescribed constituents, at least 70% of the plastic part of the Product after use shall be recovered. Furthermore, at least 70% of such recovered plastic parts shall be directed to material recycling. However, this item is not applicable to the product with 20 years or more of the average length of year to use,

even if the product uses plastics containing halogen.

[Certification Procedure]

Whether this criteria applies to the Product or not shall be stated in the Attached Certificate, and, if affirmative, a document ensuring that proper recovery and recycling will be made at the time of Product disposal, or continuous use of 20 years and more shall be submitted.

Eco Mark Office reserves the right to ask the reports on the recovery ratio (or to conduct audit) after the conclusion of the license agreement, for which the Applicant assumes the obligation to cooperate.

C. Glass cullet

- (7) As for the elution of harmful substances from glass cullet, the product shall conform to the standards concerning elution of harmful substances that are set forth in Attached Table 4 of the enforcement regulation of the Soil Contamination Countermeasures Law (2002 Ministerial Order No. 29 of the Ministry of the Environment) with respect to cadmium, lead, hexavalent chromium, arsenic, mercury, selenium, boron and fluorine among the specified hazardous substances listed therein. In addition, if waste glass is used as a raw material, color of cullet to be used (solid color, brown, etc.) shall also be reported.

[Certification Procedure]

A certificate shall be submitted describing the results of tests carried out by an independent testing institution or a public institution. If waste glass is used as a raw material, usage of solid color cullets, brown cullets or those in any other color shall also be reported.

D. Fibers

- (8) In the use of fibers, chemical materials given in Attached table 2 shall conform to the standard values.

[Certification Procedure]

Certificates shall be submitted according to Attached table 2.

E. Other materials

- (9) The Product that is made of gypsum board recycled from the waste generated in connection with building demolition shall be made free of products that are known to have contained asbestos, arsenic, or cadmium through the process of sorting and removal. On the subject of specific waste gypsum boards to be eliminated, the Applicant should refer to “On the Inclusion of Asbestos in Gypsum Boards) published by the Gypsum Board Industry Association, “Proper Handling of Hazardous Substances and the Like Associated with Building Demolition and the Like” published by the Construction By-products Recycling Promotion Conference, and other pertinent documents.

No analysis shall be required if the Product is made of gypsum board that is recycled from the waste coming out of the manufacturing process of gypsum board processing plants or generated at a new building construction site, because the

recycled material does not contain asbestos.

[Certification Procedure].

Applicants shall enter the conforming condition to this item in the attached certificate. In the event that products which have turned out to have contained asbestos, arsenic, and/or cadmium are separated and removed, applicants must report the specific separation and removal methods. Incidentally, in the case of judgment by analytical examinations, applicants must determine that more than 0.1% of six types of asbestos including Tremolite are not contained by the methods that conform to “JIS A1481: Determination of asbestos in building material products” (2008) shown in the Instruction Letter No. 0821002 of the Labour Standards Bureau of the Ministry of Health, Labour and Welfare dated August 21, 2006 “On the Analysis Method of Asbestos Content in Building Materials.”

- (10) For a product using construction sludge as a raw material, the conditions for discharging construction sludge and acceptance criteria for checking soil property shall be defined with reference to “Construction Sludge Recycling Manual” (Written and edited by Public Works Research Institute in December 2008), and only inorganic sludge that were subjected to appropriate treatment shall be used. Any construction sludge that does not conform to the environmental quality standards for soil based on the Environmental Basic Law and the content standard of specified toxic substances based on the Soil Contamination Countermeasures Law shall not be used unless it is subjected to proper processing so that it can conform to these standards.

[Certification Procedure]

Conformance to this item shall be stated in the attached certificate. A material describing conditions for receiving construction sludge, content and flow of treatment shall be submitted.

4-1-3. Individual product criteria and certification procedure

- (11) As for fenders, the product shall be made of rubber as a main material, and the mass ratio of recycled rubber shall be 10% or more of the total rubber used in the products. As for rubber materials for harbors except fenders shall be made of rubber as a main material, and the mass ratio of recycled rubber shall be 20% or more of the total rubber used in the products.

As for channel repairing panels, the total mass of recycled materials given in Tables 1 and 2 shall be 50% or more of the total mass of the product.

In cases where recycled materials in Category C in Table 1 are used, high-stability treatment, burning or verification shall be conducted in the stage of pre-treatment of raw materials or production process, based on the “Construction Sludge Recycling Manual” (Written and edited by Public Works Research Institute in December 2008)

The product in which plant-based plastic or plant-based synthetic fiber is used

may satisfy 4-1-3.(12) instead of 4-1-3.(11).

Table 1 Recycled materials usable for landscaping/revegetation materials
(excluding concrete portions)

| Recycled material | | | |
|---------------------|--|--|--|
| Category A | Reused/unused wood | | |
| | Waste plant fibers (Rice straw, palms, moss, etc.) | | |
| | Waste paper | | |
| Category B | Fiber | Unused fibers | |
| | | Recycled fibers | Recovered fibers |
| | | | Recycled polymer fibers [50] |
| | | | Recycled chemical fibers [50] |
| | Unused cloth, recycled cloth | | |
| | Mining/quarrying industry wastes | Quarrying and ceramic industry waste soil, micro-silica sand obtained during the water washing of silica sand (mica powder) | |
| | Metal industry wastes | Steel slag, foundry sand, ceramic waste, copper slag, ferro-nickel slag, electric furnace slag | |
| | Other industrial type wastes | Coal ash, recycled plastics [50], shells, Recycled rubber, glass cullet, gypsum (including desulfurized gypsum), glass wool, rock wool | |
| | Non-industrial wastes and vitrified materials in sewage sludge | | |
| | Category C | Living/self-generating sludge | Waterworks sludge, sludge from the bottom of lakes |
| Industrial sludge | | Paper-manufacturing sludge, aluminum sludge, galvanizing sludge, polishing sludge | |
| Construction sludge | | | |

Note 1: The percentage mass of wooden parts means the mass ratio of the product or each material in an air dried state^{*1} or at the point of constant weight^{*2} at a temperature of 20±2°C and humidity of 65±5%.

*1: Indicates leaving in a well-ventilated room for seven days or more.

*2: Change is less than 0.1% when the weight is measured every 24 hours.

Table 2
Recycled materials usable for concrete products

| Recycled material | Standard mixture rate |
|-------------------|-----------------------|
|-------------------|-----------------------|

| | |
|---|---|
| <ul style="list-style-type: none"> - Coarse aggregates in conformity with Category-C Certification Criteria 4-1-2.A.(2) for applicable 'aggregates - Cement in conformity with Category-C Certification Criteria 4-1-2.B.(6) to (7) for the applicable 'cement' - Concrete admixture in conformity with Category C 4-1-2.C.(11) for the applicable 'concrete admixture'. | $\frac{\text{Mass of recycled material in the product}}{\text{Mass of product}} \times 100 \geq 50$ |
| Coarse aggregates in conformity with Category-C Certification Criteria 4-1-2.A.(2) for applicable 'aggregates | $\frac{\text{Total mass of recycled material in aggregate}}{\text{Mass of aggregate}} \times 100 \geq 50$ |
| <ul style="list-style-type: none"> - Cement in conformity with Category-C Certification Criteria 4-1-2.B.(6) to (7) for the applicable 'cement' - Concrete admixture in conformity with Category-C Certification Criteria 4-1-2.C.(11) for the applicable 'concrete admixture'. | $\frac{\text{Total mass of recycled material in cement and additive}}{\text{Mass of cement + mass of additive}} \times 100 \geq 50$ |

[Certification Procedure].

A raw materials certificate issued by the supplier shall be attached. In addition, the types of recycled materials, the proportional content of recycled materials and materials other than recycled materials and control procedures shall be stated in the product weight certificate.

For thinned-out log and less useful wood, a certificate given in Attached table 3 shall be submitted.

As for the products using raw materials in Category C, a certificate that high-stability treatment, burning or melt-solidification has been conducted shall be submitted.

- (12) A product in which plant-based plastic or plant-based synthetic fiber is used shall meet all the requirements listed in a) to c) below. However, when the criteria item 4-1-3.(11) is selected, this item shall not apply.
- a) The bio-based synthetic polymer content in the entire product mass shall be 10% or higher, and the mass ratio of the plant-based plastic / synthetic fiber shall be 25% or higher.
 - b) The Applicant shall have the understanding of the supply chain from cultivation of plant materials to manufacturing of plant-based plastic (raw resin). Each process shall conform to the checklist in the Attached table 4.
 - c) The Applicant shall have confirmed by the life cycle assessment (LCA) that for the plant-based plastic (raw resin), greenhouse gas emissions (CO₂ conversion) from raw material procurement to discarding/recycling does not increase, when compared with conventional resin that is to be replaced. Note that if any increase in the emissions is offset by the reliable carbon offset (such as purchasing clean electric power, etc.), the applied product shall also conform to this item.

[Certification Procedure]

a) Certificates indicating the calculated content of biobased synthetic polymers in the entire product mass shall be submitted. For the plant-based plastic (raw resin) thereof, measurement results of the biobased synthetic polymer content calculated with the method specified in ISO 16620-3, using measurement results of the biobased carbon content and element composition by the 14C method specified in ISO 16620-2 or ASTM D6866 shall be mentioned. Should there be any deviation of 10% or higher between the measurement results and the content of biobased synthetic polymer in the standard, a description of a reason(s) therefor shall also be included. The measurement results of the biobased carbon content shall be submitted as an attached document.

In addition, for appropriate maintenance of the content of biobased synthetic polymer after certification, any of the following certificates issued by a raw resin supplier (including a dealer) shall be submitted.

- An explanatory document stating that measurements of the content of biobased carbon will be regularly carried out, and that measurement results can be disclosed as per a request of the Eco Mark Office; and
- A certificate that the Applicant has been audited or certified by a third party for management of the content of the biobased synthetic polymer.

b) Certificates issued by a raw resin supplier (including a dealer) indicating the supply chain (flow diagram, etc. and including purification, fermentation, etc.) from the cultivation area (country, state, city, etc.) to manufacturing of plant-based plastic (raw resin), and status of conformance to the Attachment shall be submitted.

c) Results of the LCA assessment of the plant-based plastic (raw resin) shall be submitted (reference to the existing paper, etc. is acceptable). If carbon offset is adopted, data describing content of the carbon offset and reliability shall be submitted together.

- (13) As for elution of harmful substances from rubber materials for harbors or channel repairing panels, the product shall conform to the standards concerning elusion of harmful substances that are set forth in Attached Table 4 of the enforcement regulation of the Soil Contamination Countermeasures Law (2002 Ministerial Order No. 29 of the Ministry of the Environment) with respect to cadmium, lead, hexavalent chromium, arsenic, mercury, selenium, boron and fluorine among the specified hazardous substances listed therein..

However, this item shall not apply to metal portions such as steel products, etc. Slags may be tested by JIS K0058-1 "Test methods for chemicals in slags". The materials listed in the 4-1-2A-D shall be in accordance with the 4-1-2 and can be omitted.

[Certification Procedure].

A certificate shall be submitted describing the results of tests carried out by an independent testing institution or public institution

- (14) Regarding impermeable-type steel erosion control weirs, a double-wall type (weirs structured using steel sheet piles for the wall surface facing upstream/downstream and connection of the wall materials with tie rods) shall be able to utilize earth and sand/gravel generated at the site as hearting materials for 70% or more of the weir volume. A steel frame type (weirs structured by combining shaped steel pieces) shall be able to utilize gravel generated at the site as hearting materials for 70% or more of the weir volume, provided that regarding the hearting materials to be used for the steel frame type, the diameter of the gravel shall be 150 mm or larger, and for the steel frame type using expanded metal for the wall materials, gravel with a diameter of 50 mm or larger shall be used.

[Certification Procedure].

The following items shall be verified.

- a. A document shall be submitted specifically describing the product specifications, including the dimensions, shape and materials.
- b. A document shall be submitted specifically describing the construction method; if multiple methods are used, each of such methods shall be indicated.
- c. A document shall be submitted specifically stating evidence that for 70% or more of the weir volume, the double-wall type is able to utilize earth and sand/gravel generated at the site and the steel frame type uses gravel generated at the site as hearting materials; if multiple construction methods are used with different evidence, the evidence for each of the respective methods shall be indicated. The types of products for application with the gravel diameters of the hearting materials shall be stated in the Attached Certificates.

- (15) Permeable-type steel erosion control weirs shall be weirs equipped for the purpose of trapping avalanches of sand and stone and at normal times to allow water, sand and gravel to flow in order to control the lowering of the river bed or the erosion of beaches, as well as to allow the movement of flora and fauna.

[Certification Procedure].

The following items shall be verified.

- a. A document shall be submitted specifically describing the product specifications, including the dimensions, shape and materials.
- b. A document shall be submitted specifically describing the construction method; if multiple methods are used, each of such methods shall be indicated.
- c. A document shall be submitted specifically stating evidence that the product, under normal conditions, allows water, sand and gravel to flow to control the lowering of the river bed and erosion of the beaches.
- d. A document shall be submitted specifically stating evidence that the product does not hinder the movement of flora and fauna; if multiple construction methods are used with different evidence, the evidence for each of such methods shall be indicated.

- (16) Special-type mat cylinders shall be mat cylinders structured with highly rigid materials such as welded wire mesh or shape steel. Harbor embankment mats, wire-cylinders and special type mat cylinders shall be able to utilize earth and sand/gravel extracted at the site as hearting materials for 70% or more of the mats or cylinders.

[Certification Procedure].

The following items shall be verified.

- a. A document shall be submitted specifically describing the product specifications, including the dimensions and materials.
- b. A document shall be submitted specifically describing the construction method; if multiple methods are used, each of such methods shall be indicated.
- c. A document shall be submitted specifically stating evidence that the product is able to utilize earth and sand/gravel extracted at the site as hearting materials for 70% or more of the mats or cylinders; if multiple construction methods are used with different evidence, the evidence for each of such methods shall be indicated.

- (17) Planting fins for revegetation, which it shall be possible to mount on steel sheet pile banks and to hold soil to provide a base growing medium for perennial emergent plants; landscaping functions to cover the steel sheet pile surface with plants shall be provided without the loss of structural functions required for revetment, such as vibration proofing, corrosion proofing, durability, etc. and planting on the banks shall be made possible.

[Certification Procedure]

The following items shall be verified.

- a. A document shall be submitted specifically describing the product specifications, including the dimensions and materials.
- b. A document shall be submitted specifically describing the construction method; if multiple methods are used, each of such methods shall be indicated.
- c. A document shall be submitted specifically stating evidence that the steel sheet pile is able to be covered by plants; if multiple construction methods are used with different evidence, the evidence for each of such methods shall be indicated.

- (18) For fish reefs and growth substrate material, sea shells are used as recycled material, and the compounding ratio of recycled material shall be 60% or more of the mass of the portion with steel products eliminated from the entire product. Products which are composed of with concrete only shall have recycled material shown in 4-1-3.(11) Table 2 used at a ratio exceeding the reference compounding ratio. The method of computing recycled material used shall be either [1] total mass of the recycled material to the product mass, [2] total mass of the recycled material in aggregate to the total mass of aggregate, or [3] total mass of recycled material in cement and additive to the total mass of cement and additive.

In the event that fish reefs, etc. installed to the sea bottom and others are damaged due to some reason, the fish reefs, etc. shall have structure that can minimize scattering of the part to the surrounding sea areas.

[Certification Procedure]

A raw materials certificate issued by the supplier shall be attached. In addition, the types of recycled materials, the proportional content of recycled materials and materials other than recycled materials and control procedures shall be stated in the product weight certificate.

Also, information materials specifically describing the product specifications of fish-breeding reefs, including dimensions, shape and quality of material, shall be submitted together with a document stating that the materials in the mixture will not scatter under the sea.

- (19) As for the elution of harmful substances from fish reefs and growth substrate material, the product shall conform to the standards concerning elusion of harmful substances that are set forth in Attached Table 4 of the enforcement regulation of the Soil Contamination Countermeasures Law (2002 Ministerial Order No. 29 of the Ministry of the Environment) with respect to cadmium, lead, hexavalent chromium, arsenic, mercury, selenium, boron and fluorine among the specified hazardous substances listed therein. However, this item shall not apply to metal portions such as steel products, etc. Slags may be tested by JIS K0058-1 “Test methods for chemicals in slags”. The materials listed in the 4-1-2A-D shall be in accordance with the 4-1-2 and can be omitted.

[Certification Procedure].

A certificate stating the test results carried out by any independent testing institution or public institution shall be submitted.

4-2. Quality Criteria and Certification Procedure

- (20) Quality requirements for the products, for which the JIS, Minister of Land, Infrastructure and Transport’s certification, standards established by local government units, standards of industrial associations or other equivalent standards have been established, shall conform to the relevant standards. Other products, for which the JIS or the equivalent has established measuring methods for quality requirement items, shall conform to the relevant similar JIS or its equivalent.

[Certification Procedure].

A certificate shall be submitted verifying conformity with the relevant quality standards.

- (21) Impermeable-type steel erosion control weirs and permeable-type steel erosion control weirs shall be given type certification from the Sabo Technical Center.

[Certification Procedure].

A certificate shall be submitted verifying conformity with the relevant quality standards.

- (22) Fish-breeding reefs and base materials for breeding shall have been designed in accordance with the guidelines for designing facilities for fishing ports and grounds (National Association of Fisheries Infrastructure Corp., 2003), and the safety, decay durability, functionality, and economic efficiency as a fish-breeding reef shall have been confirmed.

[Certification Procedure].

A document stating that it was designed in accordance with the guidelines for designing facilities for fishing ports and grounds shall be submitted.

5. Product Classification, Indication and Others

- (1) The products shall be classified according to each applicable product in “2. Applicable Scope” (Attached table 1) and brand of the product. The product is not classified by size or color; provided that products made of different materials shall be applied separately.
- (2) Regarding products which correspond to designated procurement items under the "Act on Promotion of Procurement of Eco-friendly Goods and Services by the State and Other Entities (Green Purchasing Law)", conformity status for evaluation criteria will be announced on the website of the Eco Mark Office.
- (3) In principle, Eco Mark shown as below shall be indicated on the product main body. The licensees of Eco Mark Utilization Contract who own the Eco Mark products shall also be allowed to use the indication and the certification number as before.



(Note for the indication)

- *For indicating the logo, Eco Mark certification number (eight-digit number) or the name of the licensee using the logo shall be appeared.
- * Such expression as “Eco Mark product” can be used following the 2.(2) of the Guide to Eco Mark Usage.
“Eco Mark product”, “#Eco Mark”, “www.ecomark.jp”, “Eco Mark Certificate”
- * If a licensee makes an environmental claim of the Eco Mark certified products associating with the Eco Mark logo, please comply with the “Environmental Labeling Guidelines” of the Ministry of the Environment of Japan.
(<https://www.env.go.jp/policy/hozen/green/ecolabel/guideline/>)
- * The Guide to Eco Mark Usage shall be followed for any cases not listed above.
(<https://www.ecomark.jp/office/guideline/guide/>)

| | |
|-------------------|---|
| January 15, 2005 | Established |
| February 23, 2005 | Revised (4-1-3.L(75)、(76)) |
| May 13, 2005 | Revised (4-1-3. (35)、(94), 5-1-3.(73)) |
| September 8, 2005 | Revised (Terminology) |
| April 28, 2006 | Revised |
| October 19, 2006 | Revised |
| February 9, 2007 | Revised |
| April 13, 2007 | Revised |
| October 5, 2007 | Extension of Expiration date |
| February 14, 2008 | Extension of Expiration date |
| June 9, 2008 | Revised |
| August 21, 2008 | Revised |
| May 1, 2009 | Revised |
| November 4, 2009 | Revised |
| March 1, 2011 | Revised (5.Indication, Version1.14) |
| June 15, 2012 | Revised (4-1.(4),deletion of 5.(2)(3) Version1.15) |
| February 1, 2013 | Revised (Version1.16) |
| February 1, 2014 | Extension of Expiration date |
| December 1, 2014 | Revised (Category F, Version1.17) |
| March 1, 2018 | Revised (4-1.(4), Version1.18) |
| August 10, 2018 | Revised (Category E-J, addition of 5.(2)(3) Version 1.19) |
| January 7, 2019 | Extension of Expiration date |
| April 1, 2022 | Revised (Category E, J: Version 1.20) |
| January 31, 2026 | Expiration date |

The Certification Criteria for the Product Category will be revised when necessary.

Attached table 2 Criteria for chemicals in fibers

The following chemicals shall conform to certification criteria for the respective applicable products.

As for certification, for substances given in Ref. No. 1, the fact of whether mildew proof finishing is applied shall be stated; the fungicides shall be described for mildew proof finished products. For substances given for Ref. No. 2, the fact of whether the product is a wool product shall be stated; for a wool product, a certification shall be submitted verifying that the relevant product conforms with Ministry of Health and Welfare (MHW) Ordinance No. 34. For substances given in Ref. No. 3, the fact of whether flame proofing is applied shall be stated; for flame proof products, the agents used shall be stated, or a certification shall be submitted verifying that the products are flame retardant goods or flame retardant products.

| Ref. No. | Name | Standard value | Test method | Applicable product |
|----------|--|--------------------|----------------------|--------------------|
| 1 | Organic mercury compounds Triphenyl tin compounds Tributyl tin compounds | Not to be detected | MHW Ordinance No. 34 | All the products |
| 2 | Dieldrin DTTB | 30 ppm or less | MHW Ordinance No. 34 | All the products |
| 3 | APO TDBPP Bis (2,3-dibromopropyl) phosphate compound | Not to be detected | MHW Ordinance No. 34 | All the products |

Reference: Law for the Control of Household Products Containing Hazardous substances

It shall be stated whether the following manufacturing process was used or not.

| Name of process | Items to be given consideration when processing |
|-----------------------|---|
| Fluorescent whitening | Limited to the required minimum processing and sufficient caution to be given concerning over-processing; application to be avoided for baby and infant products. |
| Flame proof finishing | Limited to the required minimum processing and sufficient caution to be given concerning over-processing |
| Softening | |
| Sanitary finishing | The use of agents whose safety for humans has been questioned is to be avoided. |
| Product bleaching | If planning to use these agents, apply to the product only after confirming its safety |

Reference: 47, Senkyoku No. 569, Director-General, Fibers and General Merchandise Bureau, Ministry of International Trade and Industries
48, Seikyoku No. 289, Director-General, Consumer Goods Industries Bureau, Ministry of International Trade and Industries
63, Seikyoku No. 226, Director-General, Consumer Goods Industries Bureau, Ministry of International Trade and Industries

Color agents given in the following (1), (2) and (3) shall not have been added as prescribed constituents.

In fibers other than wool, chromic color agents shall not have been added as prescribed constituents.

As for certification, a certificate issued by the manager of the plant manufacturing the product shall be submitted.

(1) Azo dyes that may release one or more of the carcinogenetic aromatic amines listed below

(Products in which one or more of the following amines are detected at 30 mg per kg of the product using analysis methods regulated by the official test method corpus based on the German Law on Foods and Sundries Article 35)

| Carcinogenicity rank (A1) | | |
|---------------------------|---|----------------------|
| 92-67-1 | 4-aminobiphenyl | C1(EU), 1(NTP,IARC) |
| 92-87-5 | Benzedrine | C1(EU), 1(NTP,IARC) |
| 95-69-2 | 4-chloro-o-toluidine | 2A(NTP,IARC) |
| 91-59-8 | 2-naphthylamine | C1(EU), 1(NTP,IARC) |
| Carcinogenicity rank (A2) | | |
| 97-56-3 | o-aminoazotoluene | C2(EU), 2B(NTP,IARC) |
| 99-55-8 | 2-amino-4-nitrotoluene | 3(NTP,IARC) |
| 106-47-8 | 4-chloroaniline | C2(EU), 2B(NTP,IARC) |
| 615-05-4 | 2,4-diaminoanisole | 2B(NTP,IARC) |
| 101-77-9 | 4,4'-diaminodiphenylmethane | C2(EU), 2B(NTP,IARC) |
| 91-94-1 | 3,3'-dichlorbenzidine | C2(EU), 2B(NTP,IARC) |
| 119-90-4 | o-dianisidine; 3,3'-Dimethoxybenzidine | C2(EU), 2B(NTP,IARC) |
| 119-93-7 | o-tolidine; 3,3'-Dimethylbenzidine | C2(EU), 2B(NTP,IARC) |
| 838-88-0 | 4,4'-diamino-3,3'-dimethyldiphenylmethane | C2(EU), 2B(NTP,IARC) |
| 120-71-8 | p-cresidine | 2B(NTP,IARC) |
| 101-14-4 | 4,4'-diamino-3,3'-dichlorodiphenylmethane | C2(EU), 2A(NTP,IARC) |
| 101-80-4 | 4,4'-diaminodiphenylether | 2B(NTP,IARC) |
| 139-65-1 | 4,4'-diaminodiphenylsulfide | 2B(NTP,IARC) |
| 95-53-4 | o-toluidine | C2(EU), 2B(NTP,IARC) |
| 95-80-7 | 2,4-diaminotoluene | C2(EU), 2B(NTP,IARC) |
| 137-17-7 | 2,4,5-trimethylaniline | |
| 90-04-0 | o-anisidine | C2(EU), 2B(NTP,IARC) |
| 95-68-1 | 2,4-xylidine | 3(NTP,IARC) |
| 87-62-7 | 2,6-xylidine | 2B(NTP,IARC) |
| 60-09-3 | 4-amino-azo-benzen | C2(EU) |

(2) Carcinogenic dyes

| | | | |
|-----------|------------------------|----------|-----------------------------------|
| 569-61-9 | C.I. BASIC RED 9 | CI 42500 | C2(EU), 2B(NTP,IARC), ECOTEX |
| 2475-45-8 | C.I. DISPERSE BLUE 1 | CI 64500 | C2(EU), 2B(NTP,IARC), ECOTEX |
| 3761-53-3 | C.I. ACID RED 26 | CI 16150 | 2B(NTP,IARC),ECOTEX |
| 6459-94-5 | C.I. ACID RED 114 | CI 23635 | 2B(NTP,IARC) |
| 2602-46-2 | C.I. DIRECT BLUE 6 | CI 22610 | C2,R3(EU),2A(NTP,IARC), ECOTEX |
| 1937-37-7 | C.I. DIRECT BLACK 38 | CI 30235 | C2,R3(EU), 2A(NTP,IARC),ECOTEX |
| 573-58-0 | C.I. DIRECT RED 28 | CI 22120 | C2,R3(EU) ,ECOTEX |
| 2832-40-8 | C.I. DISPERSE YELLOW 3 | CI 11855 | ECOTEX |

(3) Skin sensitizing dyes

| | | | |
|------------|-------------------------|----------|-------------|
| 2475-46-9 | C.I. DISPERSE BLUE 3 | CI 61505 | ETAD,ECOTEX |
| 12222-75-2 | C.I. DISPERSE BLUE 35 | | ETAD,ECOTEX |
| | C.I. DISPERSE BLUE 106 | | ETAD,ECOTEX |
| | C.I. DISPERSE BLUE 124 | | ETAD,ECOTEX |
| 2832-40-8 | C.I. DISPERSE YELLOW 3 | CI 11855 | ETAD,ECOTEX |
| 730-40-5 | C.I. DISPERSE ORANGE 3 | CI 11005 | ETAD,ECOTEX |
| | C.I. DISPERSE ORANGE 37 | | ETAD,ECOTEX |
| 2872-52-8 | C.I. DISPERSE RED 1 | CI 11110 | ETAD,ECOTEX |
| 2475-45-8 | C.I. DISPERSE BLUE 1 | CI 64500 | ECOTEX |
| 3179-90-6 | C.I. DISPERSE BLUE 7 | CI 62500 | ECOTEX |
| 3860-63-7 | C.I. DISPERSE BLUE 26 | CI 63305 | ECOTEX |
| | C.I. DISPERSE BLUE 102 | | ECOTEX |
| | C.I. DISPERSE ORANGE 1 | CI 11080 | ECOTEX |
| | C.I. DISPERSE ORANGE 76 | | ECOTEX |
| 2872-48-2 | C.I. DISPERSE RED 11 | CI 62015 | ECOTEX |
| | C.I. DISPERSE RED 17 | CI 11210 | ECOTEX |
| 119-15-3 | C.I. DISPERSE YELLOW 1 | CI 10345 | ECOTEX |
| | C.I. DISPERSE YELLOW 9 | CI 10375 | ECOTEX |
| | C.I. DISPERSE YELLOW 39 | | ECOTEX |
| | C.I. DISPERSE YELLOW 49 | | ECOTEX |

Reference: International Agency for Research on Cancer (IARC)

National Toxicology Program (NTP)

EU Directive 76/769/EC

EU Directive 2002/61/EC

The Ecological and Toxicological Association of Dyes and Organic Pigments
Manufacturers (ETAicD) ECOTEX STANDARD 100

Attached table 3 Criteria and certification for thinned out wood and less useful wood

If using thinned wood as the material, a certificate of origin that includes information on the place of production, type of tree, and year of planting shall be submitted with photographs of the forest concerned (showing clearly that the forest stand has been thinned). The thinning percentage and how many times the forest stand has been thinned, including the most recent thinning shall also be indicated if possible.

If using less useful wood, the following information shall be submitted. At the same time, official documents stating that the forest has been certified as sustainable by a third party shall be submitted.

- Type of forest (natural or man-made, etc.), place of production, type of tree, and year of tree planting if man-made forest.
- Under what conditions was the wood produced (damaged by disease/pests, damaged by disaster, bent or narrow trees, etc.). For small diameter log, indicate logging method and tip end diameter.

If small-diameter wood of less useful wood is used, and if it applies to a or b described below, a document certifying that forests were certified as sustainable by a third party as listed in the table below shall also be submitted.

- a. Small diameter logs from logs felled from natural forests.
- b. Small diameter logs from logs produced by clear cutting, patch logging, and strip logging in plantation forests.

Table Requirements for Forest Certification

| | |
|------------------------|---|
| Certification criteria | - While balancing economical, ecological, and social benefits, the criteria shall comply with Agenda 21 and Statement of Principles on Forests, and observe related international agreements and conventions. |
| | - Including solid requirements, the criteria shall promote sustainable forests. |
| | - Recognized both domestically and internationally, the criteria shall be recommended as part of the process opened to participation by ecological, economical, and social stakeholders. |
| Certification system | - Certification systems shall have high transparency, maintain nation-wide or international reliability, and can verify requirements. |
| Certification body | - With fairness and high reliability, certification organizations and groups shall be able to verify that requirements are satisfied, convey the results, and able to execute requirements effectively. |

If using bamboo as the raw material in less useful wood, certificates indicating the following information and photographs/maps of the surroundings of the bamboo grove shall be submitted.

- Type of bamboo, place of production, surrounding conditions, and description that logging is carried out for the purpose of appropriate maintenance and management in environment preservation, as well as management plans and quantity.

Attached table 4 Checklist of Traceability of Plant-based Plastic (Raw Resin)

| No | Purpose | Request (Item that must be realized) | Subject | Realized | Implementation Method (Check off all relevant items.) |
|----|---|---|-----------|---|--|
| 1 | Prevention of global warming, conservation of the natural ecosystem | Hasn't the farm land where plants are cultivated been converted from forests in the recent ten years? | Farm land | <input type="checkbox"/> Yes/ <input type="checkbox"/> No | <input type="checkbox"/> Confirmed the laws and regulations concerning the land conversion for the site. <input type="checkbox"/> Gained the understanding of the actual condition of the site through on-site investigation or hearings. <input type="checkbox"/> Defined and released the guideline for procurement of plants. Alternatively, conforming to the guideline of an independent third party. - Name of the guideline: - Location of release: <input type="checkbox"/> Also using the certification system of an independent third party, regarding the procurement of plants. -Name of certification system: <input type="checkbox"/> Others (Describe specifically.): |
| 2 | Conservation of the ecosystem | If the Applicant uses the genetically engineered crop as a raw material, has the Applicant assessed ensuring of safety? | Farm land | <input type="checkbox"/> Yes/ <input type="checkbox"/> No/ <input type="checkbox"/> Not applicable (Not used) | <input type="checkbox"/> Confirmed the laws and regulations concerning genetically engineered crop on the site. <input type="checkbox"/> Gained the understanding of the actual condition of the site through on-site investigation or hearings. <input type="checkbox"/> Defined and released the guideline for procurement of plants. Alternatively, conforming to the guideline of an independent third party. - Name of the guideline: - Location of release: <input type="checkbox"/> Also using the certification system of an independent third party, regarding the procurement of plants. -Name of certification system: <input type="checkbox"/> Others (Describe specifically.): |

| No | Purpose | Request (Item that must be realized) | Subject | Realized | Implementation Method (Check off all relevant items.) |
|----|--|---|-----------|--|---|
| 3 | Prevention of land acidification/nutrient enrichment/water contamination | Has the Applicant gained the understanding of usage conditions of fertilizers/agricultural chemicals in the main cultivation area of plants? Isn't any agricultural chemical regulated under the "Stockholm Convention on Persistent Organic Pollutants" (POPs Treaty) used? | Farm land | <input type="checkbox"/> Yes/ <input type="checkbox"/> No | <input type="checkbox"/> Confirmed the laws and regulations concerning fertilizers/agricultural chemicals on the site <input type="checkbox"/> Gained the understanding of the actual condition of the site through on-site investigation or hearings. <input type="checkbox"/> Defined and released the guideline for procurement of plants. Alternatively, conforming to the guideline of an independent third party. - Name of the guideline: - Location of release: <input type="checkbox"/> Also using the certification system of an independent third party, regarding the procurement of plants. -Name of certification system: <input type="checkbox"/> Others (Describe specifically.): |
| 4 | Appropriate water usage | Has the Applicant gained the understanding of usage conditions of water in the main cultivation area of plants? | Farm land | <input type="checkbox"/> Yes/ <input type="checkbox"/> No | <input type="checkbox"/> Confirmed the laws and regulations concerning usage of water (limits on the amount of water) on the site. <input type="checkbox"/> Gained the understanding of the actual condition of the site through on-site investigation or hearings. <input type="checkbox"/> Defined and released the guideline for procurement of plants. Alternatively, conforming to the guideline of an independent third party. - Name of the guideline: - Location of release: <input type="checkbox"/> Also using the certification system of an independent third party, regarding the procurement of plants. -Name of certification system: <input type="checkbox"/> Others (Describe specifically.): |

